

Housing Plus 3P - SX



Housing Plus 3P SX
for cartridges with standard flat seals (SX)
in single and duplex layout



Applications:

Filtration and treatment of water with neutral pH and drinking water.

Domestic use: Filtration and treatment of drinking water, protection of taps, boilers, washing machines and other installation.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine removing appliances, reverse osmosis units.

Working conditions:

Max working pressure = 8 bar

Max working temperature = 45°C

Specifications:

Non-toxic materials, suitable for drinking water.

Head and nut ring: reinforced polypropylene

Transparent bowl: SAN

O-ring: ETP.

IN / OUT threads brass inserts

Available types single housing:

Height	Type	in/out
10"	Senior Plus 3P AFO SX AS	3/4"
10"	Senior Plus 3P BFO SX AS	1"
20"	Master Plus 3P AFO SX AS	3/4"
20"	Master Plus 3P BFO SX AS	1"

Height	Type	in/out
10"	Duplex Senior Plus 3P AFO SX AS	3/4"
20"	Duplex Master Plus 3P AFO SX AS	3/4"

Available types Duplex housing:

Accessories / options:

- N-spanner (key for easy opening and closing)

the filter houses, see picture below)

- Wall bracket (only for single houses)
- AB series (with opaque blue bowl, impermeable to the light)



Wound or melt blown polypropylene filtering medium for pre filtration



melt blown or wound polypropylene filtering medium, from 1 to 50 micron

Applications

Sediment filter for sand, scale, lime, rust and fine particles

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines e.d.

Average life-span: 3 -6 months

Max working temperature: 45°C

Senior 10" : wound FA 10 SX (1000 l/h) or melt blown MA 10 SX (1000 l/h)

Master 20" : wound FA 20 SX (2000 l/h) or melt blown MA 20 SX (2000 l/h)

