

Teledyne Isco Samplers

Water Technology Ltd are exclusive Irish dealers for ISCO Auto Samplers since 1992. We provide both stationary or portable, refrigerated or non-refrigerated, single or multi-bottle. Applications include IPC licence, Inlet and Outlet sampling of WWTP's, product loss monitoring, environmental monitoring and more.

Our range of ISCO samplers include:



Isco 5800 Refrigerated Sampler. A stationary outdoor rated and M certified refrigerated sampler installed in hundreds of WWTP;s and industrial effluents plants throughout Ireland.

- Composite or sequential sampling
- Operating range of -20 to 120°F (-29 to 49°C) without additional heaters
- Four digital alarm outputs
- 4-20 mÅ and DC pulse flow meter input
- Powerful compressor delivers energy-efficient, high- performance cooling

Isco GLS Sampler. A non-refrigerated, single-bottle, cost –effective, sampler which can be provided as a stand alone portable or mounted in an enclosure for stationary applications.

- Overall diameter is only 16.5 inches (42 cm), so GLS fits easily into manholes as small as 18 inches (46 cm), and also easily drops into most offset manholes.
- Dry weight is less than 25 lbs (12 kg), the lightest sampler in the Isco line.
- Hinged handle makes one-handed carrying easy.
- The patented LD90 Liquid Presence Detector and Isco pump revolution counting system deliver accurate, repeatable sample volumes time after time.



Isco 6712 Sampler. A multi-bottle portable sampler with highly intelligent and versatile programming functionality. It has a built in logger and can be provided with optional plug-in flow modules. It used extensively wherever multi-bottle sampling is required and is also our standard hire sampler.

- SDI-12 interface provides "plug and play" connection with multiparameter water-quality sondes and other compatible devices.
- Standard 512kB memory gives you great flexibility for logging environmental data.
- Choice of 11 different glass and plastic bottle configurations ranging from 24 x 1 liter to 1 x 5.5 gallon.
- NEMA 4X, 6 (IP67) controller enclosure
- Rugged ABS plastic shell
- Foam-insulated base holds up to 30 pounds (13.5 kg) of ice to preserve samples even in extreme conditions.
- Sample delivery at the EPA-recommended velocity of 2 ft/sec., even at head heights of 26 feet.
- Pump revolution counter and patented liquid detection sensor ensure accuratesample volumes and tells you when tubing should be replaced.



Isco Blzzrd Portable Refrigerated Sampler

BLZZRD is a portable refrigerated sampler with active cooling from either AC or battery power. Its controller offers all advanced controls, interfaces, data logging, and remote communication features.





Applications:

- Stormwater Runoff Compliance
- TMDL and Watershed monitoring
- Enforcement Monitoring
- Anywhere you need advanced sampling capability combined with data logging and communications for flow, rainfall, and water quality parameters—plus reliable, on-demand cooling

Standard Features:

- Standard and extended programming keeps setup simple when you don't need advanced features
- NEMA 4x, 6 (IP67) controller enclosure is watertight and dustproof
- SDI-12 interface provides "plug and play" connection with multi-parameter water-quality sondes and other compatible devices
- Standard 512kB memory gives you great flexibility for logging environmental data
- NEMA 4X, 6 (IP67) controller enclosure

All our samplers come with complete technical support and after sales services. We carry all parts and consumables in Cork. We also **hire** portable samplers.